

## Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

### NATURAL GAS MARKERS ON A ROLL



Natural Gas Markers are supplied in Roll form containing 100 labels at 3 x 1"



### Typical Installation

**Compliance:**

- National Plumbing Codes

- **LEED Compliance:** This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). The adhesive backing on this product contains < 4.4 grams / Liter VOC.

**Use:**

These markers are designed to be used on copper gas lines and are perfect for residential construction.

Some areas of the country allow copper lines to be used for Natural Gas and LP Gas, as long as the lines are properly identified every 12"

**Material:**

Outdoor Grade 3.2 mil thick high gloss adhesive backed calendered vinyl film, printed using UV and chemical resistant inks, to ensure durability in most commercial / industrial environments.

**Adhesive:**

Aggressive Solvent Based Adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces.

**Surface Preparation:**

Surface must be dry and clean prior to applying adhesive backed label product. Min. Surface Temperature 50°F (10°C).

Outdoor Durability: 4 to 5 years Mid Continental US

Abrasion Resistance: Good

Water Resistance: Good

Solvent Resistance: Good

Service Temp: -20°F (-29°C) to 200°F (93°C)

Storage Stability: 2 years at 70°F (21°C) with 50 RH

DATE: / /

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_