



## Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

# System #3 Pipe Markers (Continuous Markers on a Roll)

### SIZE CHART

MARKER STYLE	OUTSIDE PIPE DIAMETER	CHARACTER SIZE	ROLL DIMENSIONS	LEGENDS PER ROLL
Small	3/4" - 2-3/8" 19mm to 60 mm	3/4" 19mm	8" Roll 203mm	240
Large	2-1/2" - 7-7/8" 64mm to 200mm	1-1/4" 32mm	12" Roll 305mm	144

### STANDARD COLORS

Flammable & Oxidizing Fluids	Potable, Cooling, Boiler Feed, Waters
Compressed Air	Fire Quenching Fluids
Toxic, Corrosive Fluids	Combustible Fluids
NFPA 99 Colors	NFPA 99 Colors
NFPA 99 Colors	NFPA 99 Colors
NFPA 99 Colors	NFPA 99 Colors
NFPA 99 Colors	* New 2015 color classification



#### Compliance:

- ANSI / ASME A13.1-2015 "Scheme for the Identification of Piping Systems"
- ANSI Z535.1 "Safety Color Code"
- NFPA 99 2015 Health Care Facilities Code
- **LEED Compliance:** This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). The adhesive backing on this product contains < 4.4 grams / Liter VOC.

#### Material:

Outdoor Grade 3.2 mil thick high gloss adhesive backed calendared vinyl film, printed using UV and chemical resistant inks, to insure durability in most commercial / industrial environments.

#### Use:

Identify piping systems. Typically installed by wrapping the label completely around the pipe to provide a 360° visible marker. Legends and arrows are printed repeatedly in opposite directions to allow the label to be applied in any direction achieving proper reading while indicating pipe content flow.

#### Adhesive:

Aggressive Permanent Adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces.

#### Surface Preparation:

Surface must be dry and reasonably clean prior to applying adhesive backed label product. Minimum Surface Temperature 50° F (10°C).

**Outdoor Durability:** 4 to 5 years Mid Continental US

**Abrasion Resistance:** Good

**Water Resistance:** Good

**Solvent Resistance:** Good

**Service Temp:** -20°F (-29°C) to 200°F (93°C)

**Storage Stability:** 2 years at 70°F with 50 RH

DATE: / /

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_