

Product Information Bulletin

P.O. Box 467 | 64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

PROMARK™ VALVE TAGS



Reinforced Lexan & Polycarbonate Nameplate

Material:

Vinyl film sealed between 2 layers of polycarbonate

Thickness:

Combined thickness of .125"

Use:

Tags are used for the identification of piping & valve tags under harsh chemical and environmental conditions.

Printed Image:

Printed image is sealed between 2 layers of polycarbonate.

Legends can be configured to almost any size type and font on multiple lines if necessary.

Mounting Method:

One 3/16" Grommetted Hole

Durability:

Indoor - Indefinite

Outdoor 5-8 years mid-continental United States

(Luminescent plates are not recommended for outdoor use)

Chemical Resistance:

Good for most chemicals

Service Temperature:

-40°F to 200°F.

Dimensional Information:

Tags are available in (2) two different sizes:

1½" & 2" Round, 1½" & 2" Square (Custom sizes available)

COLORS AVAILABLE

Background	Lettering
White	Black
Red	White
Yellow	Black
Blue	White
Green	White

Letter Sizes:

Letter sizes are determined by size of tag, number of lines, and number of characters per line.

DATE: ____ / ____ / ____

JOB: _____

CONTRACTOR: _____