



Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

EZ Voltage Markers

<p>1 Marker @ 1-1/8 x 8" Text Size: 1/2"</p> 	<p>1 Marker @ 2-1/4 x 9" Text Size: 1-1/4"</p> 	<p>9 Markers @ 1 x 2-1/4" each Text Size: 1/2"</p> 
--	---	--

Typical Installation



MARKER STYLE	MARKER DIMENSIONS	SIZE OF LETTERS
1XSME	1-1/8 x 8" / 29 x 203mm	1/2" / 13mm
1E	2-1/4 x 9" / 57 x 229mm	1-1/4" / 32mm
9E	1 x 2-1/4" / 25 x 57mm	1/2" / 13mm

Compliance:

- ANSI / ASME A13.1-2015 "Scheme for the Identification of Piping Systems"
- ANSI Z535.1 "Safety Color Code"

• **LEED Compliance:** This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). The adhesive backing on this product contains < 4.4 grams / Liter VOC.

Material:

Outdoor Grade 3.2 mil thick high gloss adhesive backed calendared vinyl film, printed using UV and chemical resistant inks, to ensure durability in most commercial / industrial environments.

Use:

Identify piping systems. EZ Pipe Markers used in conjunction with EZ Matching Arrow or Arrow Banding Tapes to identify both, pipe content and directional flow for full compliance with ANSI / ASME A13.1-2015.

Adhesive:

Aggressive Permanent Adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces.

Surface Preparation:

Surface must be dry and reasonably clean prior to applying adhesive backed label product.
Minimum Surface Temperature 50° F.

Outdoor Durability: 4 to 5 years Mid Continental US

Abrasion Resistance: Good

Water Resistance: Good

Solvent Resistance: Good

Service Temp: -20°F (-29°C) to 200°F (93°C)

Storage Stability: 2 years at 70°F with 50 RH

DATE: / /

JOB: _____

CONTRACTOR: _____