



Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

Wrap-Around Pipe Markers on a Roll

SIZE CHART

MARKER STYLE	OUTSIDE PIPE DIAMETER	CHARACTER SIZE	ROLL DIMENSIONS	LEGENDS PER ROLL
Small	3/4" - 2-3/8" 19mm to 60 mm	3/4" 19mm	8" Roll 203mm	240
Large	2-1/2" - 7-7/8" 64mm to 200mm	1-1/4" 32mm	12" Roll 305mm	144

STANDARD COLORS

Flammable, Combustible, or Oxidizing	Potable, Cooling, or Other Cold or Tepid Water
Compressed Air	Firefighting
Toxic or Corrosive	Steam; or Steam Condensate, Boiler Feedwater, or Other Hot Water
Defined By User	Defined By User
Defined By User	Defined By User
Defined By User	Defined By User



Compliance:

- ANSI / ASME A13.1-2023 "Scheme for the Identification of Piping Systems"
- ANSI Z535.1 "Safety Color Code"
- NFPA 99 Health Care Facilities Code
- **LEED Compliance:** This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). The adhesive backing on this product contains < 4.4 grams / Liter VOC.

Material:

Outdoor Grade 3.2 mil thick high gloss adhesive backed calendared vinyl film, printed using UV and chemical resistant inks, to insure durability in most commercial / industrial environments.

Use:

Identify piping systems. Typically installed by wrapping the label completely around the pipe to provide a 360° visible marker. Legends and arrows are printed repeatedly in opposite directions to allow the label to be applied in any direction achieving proper reading while indicating pipe content flow.

Adhesive:

Aggressive Permanent Adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces.

Surface Preparation:

Surface must be dry and reasonably clean prior to applying adhesive backed label product. Minimum Surface Temperature 50° F (10°C).

Outdoor Durability: 4 to 5 years Mid Continental US

Abrasion Resistance: Good

Water Resistance: Good

Solvent Resistance: Good

Service Temp: -20°F (-29°C) to 200°F (93°C)

Storage Stability: 2 years at 70°F with 50 RH

DATE: / /

JOB: _____

CONTRACTOR: _____