



Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

Self-Adhesive Pipe Markers

NATURAL GAS

3 Typical Installations



- 1 Self-Adhesive Marker with Self-Adhesive Arrow
- 2 Self-Adhesive Marker with Arrow Banding Tape
- 3 Self-Adhesive Marker with Banding Tape & Self-Adhesive Arrow

STANDARD COLORS

Color	Meaning
Red	Firefighting
Yellow	Flammable, Combustible, or Oxidizing
Green	Potable, Cooling, or Other Cold or Tepid Water
Purple	Defined By The User
Brown	Defined By The User
White with black border	Defined By The User
Yellow with black border	Defined By The User
Black with white border	Defined By The User
White with black diagonal stripes	Defined By The User
Black with white diagonal stripes	Defined By The User

DIRECTIONAL FLOW

MARKER STYLE	OUTSIDE PIPE DIAMETER	MARKER DIMENSIONS	RECOMM. MAX. CHARACT.	SIZE OF LETTERS	ALTERN. MATCHING ARROW	ALTERN. ARROW TAPE
1XSM	3/4" - 1-1/4" 19 - 32mm	8 x 1-1/8" 203 x 29mm	22	1/2 inch 13mm	4 x 1-1/8" 102 x 29mm	1" 25.4mm
1SM	1-1/2" - 2-3/8" 38 - 60mm	8 x 1-1/8" 203 x 29mm	18	3/4 inch 19mm	4 x 1-1/8" 102 x 29mm	1" 25.4mm
1	2 1/2" - 7-7/8" 64 - 200mm	14 x 2-1/4" 356 x 57mm	22	1-1/4 inch 32mm	6 x 2-1/4" 152 x 57mm	2" 51mm
1LG	8" - 10" 203 - 254mm	24 x 4" 610 x 102mm	22	2-1/2 inch 64mm	7 x 4" 178 x 102mm	2" or 4" 51 or 102mm
1XLG	OVER 10" Over 254mm	32 x 4" 813 x 102mm	22	3-1/2 inch 89mm	7 x 4" 178 x 102mm	2" or 4" 51 or 102mm

Compliance:

- ANSI / ASME A13.1-2023 "Scheme for the Identification of Piping Systems"
- ANSI Z535.1 "Safety Color Code"
- NFPA 99 Health Care Facilities Code
- LEED Compliance: This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). The adhesive backing on this product contains < 4.4 grams / Liter VOC.
- RoHS3, EU Directive 2015/863/EU Compliant: Yes
- REACH SVHC (SVHC Candidate list of June 2020): Yes
- California Proposition 65: Yes

Material:

Outdoor Grade 3.2 mil thick high gloss adhesive backed calendared vinyl film, printed using UV and chemical resistant inks, to ensure durability in most commercial / industrial environments.

Use: Identify piping systems. Self-Adhesive Pipe Markers used in conjunction with Self-Adhesive Matching Arrow or Arrow Banding Tapes to identify both, pipe content and directional flow for full compliance with ANSI / ASME A13.1

Adhesive:

Aggressive permanent acrylic adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces.

Surface Preparation:

Surface must be dry and reasonably clean prior to applying adhesive backed label product. Minimum Surface Temperature 50°F (10°C).

Outdoor Durability: 4 to 5 years Mid Continental US

Abrasion Resistance: Good

Water Resistance: Good

Solvent Resistance: Good resistance to most petroleum solvents and lower aliphatic alcohols

Service Temp: -20°F (-29°C) to 200°F (93°C)

Storage Stability: 2 years at 60°F to 80°F (16°C to 27°C) and 40-60% R.H

DATE: / /

JOB: _____

CONTRACTOR: _____