




Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

Premium Arrow Banding Tape



When determining how much tape to order be aware of the following:

- Premium Arrow Banding Tape is 30 yards long.
- Most people will apply tape on both ends of the pipe marker resulting in 2 bands per marker see typical installation image above)
- Table below provides the quantity of **bands** for an specific O.D. (Outside Diameter), not the quantity of markers.



Typical Installation
EZ Marker with Arrow Banding Tape

Pipe Diameter	1" (25.4mm)	2" (51mm)	3" (76mm)	4" (102mm)	5" (127mm)	6" (152mm)	7" (178mm)	8" (203mm)	9" (229mm)	10" (254mm)	12" (305mm)
30 Yard (90')	308	154	102	77	61	51	44	38	34	30	25

Tape Size		Recommended Pipe Size		Marker Style
1" x 30 yds.	25.4mm x 27.4m	Up to 2-3/8"	Up to 60mm	1XSM & 1SM
2" x 30 yds.	51mm x 27.4m	2-1/2" to 7-3/8"	64 to 187mm	1
4" x 30 yds.	102mm x 27.4m	Over 8"	Over 203mm	1LG & 1XLG

Compliance:

- ANSI / ASME A13.1 2020 "Scheme for the Identification of Piping Systems"
- ANSI Z535.1 "Safety Color Code"
- **LEED Compliance:** This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). The adhesive backing on this product contains < 4.4 grams / Liter VOC.
- RoHS3, EU Directive 2015/863/EU Compliant: Yes
- REACH SVHC (SVHC Candidate list of June 2020): Yes
- California Proposition 65: Yes

Material: Outdoor Grade 3.2 mil thick high gloss adhesive backed calendered vinyl film, printed using UV and chemical resistant inks, to insure durability in most commercial / industrial environments.

Use: Liner mounted adhesive tape. Banding & Arrow Tapes are often used in conjunction with EZ Pipe Markers to identify directional flow of pipe content and to fully comply with ANSI /ASME A13.1. Tape provides a 360° visible color code and locator for the actual marker, which indicates pipe content.

Adhesive: Aggressive Permanent Adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces.

STANDARD COLORS

Flammable & Oxidizing Fluids	Potable, Cooling, Boiler Feed, Waters
Compressed Air	Fire Quenching Fluids
Toxic, Corrosive Fluids	Combustible Fluids
NFPA 99 Colors	NFPA 99 Colors

Surface Preparation:

Surface must be dry and reasonably clean prior to applying adhesive backed label product. Minimum Surface Temperature 50°F (10°C).

Outdoor Durability: 4 to 5 years Mid Continental US

Abrasion Resistance: Good

Water Resistance: Good

Solvent Resistance: Good resistance to most petroleum solvents and lower aliphatic alcohols

Service Temp: -20°F (-29°C) to 200°F (93°C)

Storage Stability: 2 years at 60°F to 80°F

(16°C to 27°C) and 40-60% R.H

DATE: ___ / ___ / ___ JOB: _____

CONTRACTOR: _____