


# **Product Information Bulletin**

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809





## SIZE CHART

| MARKER<br>STYLE | OUTSIDE PIPE<br>DIAMETER |            | MARKER<br>DIMENSIONS |                        | SIZE OF<br>LETTERS |      |
|-----------------|--------------------------|------------|----------------------|------------------------|--------------------|------|
| Small           | 3/4" - 2-3/8"            | 19 x 60mm  | 8 x 1"               | 203 x 25.4mm           | 3/4"               | 19mm |
| Large           | 2-1/2"- 7-7/8"           | 64 x 200mm | 14 x 2-1             | <b>/4</b> " 356 x 57mm | 1-1/4'             | 32mm |

## STANDARD COLORS

| Flammable & *Oxidizing Fluids | Potable, Cooling, Boiler Feed, Waters |  |  |
|-------------------------------|---------------------------------------|--|--|
| Compressed Air                | Fire Quenching Fluids                 |  |  |
| Toxic, Corrosive Fluids       | Combustible Fluids                    |  |  |
| NFPA 99 Colors                | NFPA 99 Colors                        |  |  |
| NFPA 99 Colors                | NFPA 99 Colors                        |  |  |
| NFPA 99 Colors                | * New 2015 color classification       |  |  |

#### Compliance:

- ANSI / ASME A13.1-2015 "Scheme for the Identification of Piping Systems"
- ANSI Z535.1 "Safety Color Code"
- NFPA 99 2015 Health Care Facilities Code
- LEED Compliance: This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). The adhesive backing on this product contains < 4.4 grams / Liter VOC.

#### Material:

Outdoor Grade 3.2 mil thick high gloss adhesive backed calendered vinyl film, printed using UV and chemical resistant inks, to insure durability in most commercial / industrial environments.

#### Use:

Identify piping systems. Pipe Markers and Arrows are provided in conventional rolls of 50. Rolls are slitted between each marker and arrow to allow for easy installation of the arrow in any direction.

### Adhesive:

Aggressive Permanent Adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces. Storage Stability: 2 years at 70°F (21°C) with 50 RH

#### Surface Preparation:

Surface must be dry and reasonably clean prior to applying adhesive backed label product. Minimum Surface Temperature 50°F (10°C).

Outdoor Durability: 4 to 5 years Mid Continental US

Abrasion Resistance: Good Water Resistance: Good Solvent Resistance: Good

**Service Temp:** -20°F (-29°C) to 200°F (93°C)

| DATE: / /   | JOB: |  |
|-------------|------|--|
| CONTRACTOR: |      |  |