



## Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

# EZ Pipe Markers (Stick On Pipe Labels)



# GASOLINE

## DANGER

REFERENCE SDS TO LEARN ABOUT HAZARD AND PRECAUTIONARY STATEMENTS

### STANDARD COLORS

Flammable & Oxidizing Fluids	Potable, Cooling, Boiler Feed, Waters
Compressed Air	Fire Quenching Fluids
Toxic, Corrosive Fluids	Combustible Fluids
NFPA 99 Colors	NFPA 99 Colors
NFPA 99 Colors	NFPA 99 Colors
NFPA 99 Colors	NFPA 99 Colors
NFPA 99 Colors	NFPA 99 Colors

### DIRECTIONAL FLOW

MARKER STYLE	OUTSIDE PIPE DIAMETER	MARKER DIMENSIONS	GHS PICTOGRAM SIZE	CHEMICAL NAME SIZE	ALTERN. MATCHING ARROW	ALTERN. ARROW TAPE
1XSM	3/4" - 1-1/4" 19 - 32mm	8 x 1-1/8" 203 x 29mm	1/2 inch 13mm	1/2 inch 13mm	4 x 1-1/8" 102 x 29mm	1" 25.4mm
1SM	1-1/2" - 2-3/8" 38 - 60mm	8 x 1-1/8" 203 x 29mm	3/4 inch 19mm	3/4 inch 19mm	4 x 1-1/8" 102 x 29mm	1" 25.4mm
1	2 1/2" - 7-7/8" 64 - 200mm	14 x 2-1/4" 356 x 57mm	1-1/4 inch 32mm	1-1/4 inch 32mm	6 x 2-1/4" 152 x 57mm	2" 51mm
1LG	8" - 10" 203 - 254mm	24 x 4" 610 x 102mm	2-1/2 inch 64mm	2-1/2 inch 64mm	7 x 4" 178 x 102mm	2" or 4" 51 or 102mm

#### Compliance:

- ANSI / ASME A13.1-2020 "Scheme for the Identification of Piping Systems"
- ANSI Z535.1 "Safety Color Code"
- NFPA 99 Health Care Facilities Code

**LEED Compliance:** This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). The adhesive backing on this product contains < 4.4 grams / Liter VOC.

#### Material:

Outdoor Grade 3.2 mil thick high gloss adhesive backed calendared vinyl film, printed using UV and chemical resistant inks, to ensure durability in most commercial / industrial environments.

**Use:** Identify piping systems. EZ Pipe Markers used in conjunction with EZ Matching Arrow or Arrow Banding Tapes to identify both, pipe content and directional flow for full compliance with ANSI / ASME A13.1-2020.

#### Adhesive:

Aggressive permanent adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces.

#### Surface Preparation:

Surface must be dry and reasonably clean prior to applying adhesive backed label product. Minimum Surface Temperature 50°F (10°C).

**Outdoor Durability:** 4 to 5 years Mid Continental US

**Abrasion Resistance:** Good

**Water Resistance:** Good

**Solvent Resistance:** Good

**Service Temp:** -20°F (-29°C) to 200°F (93°C)

**Storage Stability:** 2 years at 70°F (21°C) with 50 RH

DATE: / /

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_