



Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

System #2 Pipe Markers (Stick On Labels on a Roll)



SIZE CHART

| MARKER STYLE | OUTSIDE PIPE DIAMETER | MARKER DIMENSIONS | SIZE OF LETTERS |
|--------------|----------------------------|------------------------|-----------------|
| Small | 3/4" - 2-3/8" 19 x 60mm | 8 x 1" 203 x 25.4mm | 3/4" 19mm |
| Large | 2-1/2" - 7-7/8" 64 x 200mm | 14 x 2-1/4" 356 x 57mm | 1-1/4" 32mm |

STANDARD COLORS

| | |
|------------------------------|---------------------------------------|
| Flammable & Oxidizing Fluids | Potable, Cooling, Boiler Feed, Waters |
| Compressed Air | Fire Quenching Fluids |
| Toxic, Corrosive Fluids | Combustible Fluids |
| NFPA 99 Colors | NFPA 99 Colors |
| NFPA 99 Colors | NFPA 99 Colors |
| NFPA 99 Colors | NFPA 99 Colors |

Compliance:

- ANSI / ASME A13.1 2020 "Scheme for the Identification of Piping Systems"
- ANSI Z535.1 "Safety Color Code"
- NFPA 99 Health Care Facilities Code
- **LEED Compliance:** This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). The adhesive backing on this product contains < 4.4 grams / Liter VOC.

Material:

Outdoor Grade 3.2 mil thick high gloss adhesive backed calendered vinyl film, printed using UV and chemical resistant inks, to insure durability in most commercial / industrial environments.

Use:

Identify piping systems. Pipe Markers and Arrows are provided in conventional rolls of 50. Rolls are slitted between each marker and arrow to allow for easy installation of the arrow in any direction.

Adhesive:

Aggressive Permanent Adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces.

Surface Preparation:

Surface must be dry and reasonably clean prior to applying adhesive backed label product. Minimum Surface Temperature 50°F (10°C).

Outdoor Durability: 4 to 5 years Mid Continental US

Abrasion Resistance: Good

Water Resistance: Good

Solvent Resistance: Good

Service Temp: -20°F (-29°C) to 200°F (93°C)

Storage Stability: 2 years at 70°F (21°C) with 50 RH

DATE: ___ / ___ / ___ JOB: _____

CONTRACTOR: _____