

Product Information Bulletin

P.O. Box 467 | 64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

Barricade Tapes

Increase Visibility Of Hazards And Prevent Accidents With Our Plastic Barricade Tapes

Tape Description:

- Our Barricade Tapes meet OSHA 1910.144 for marking physical hazards.
- Tape is a lightweight, economical, reusable polyethylene.
- Continuous repeat of warning message.
- Our barricade tapes can be tied, stapled or nailed in place.
- Tape consists of high visibility safety yellow polyethylene (plastic) with bold black letters.
- Indoor and Outdoor use.

Tape Size: 3in. x 1000 ft.

Standard letter height: 2 in.

Material Thickness: 4 Mil Polyethylene

Tape Weight: 4.5 lbs.

Test Procedure: ASTM-D-882, Method A

Specimen Conditions: 73°F / 50% R.H.

Test Temperature: 73°F

Elongation: 552%

Tensile Strength (Transverse): 2,100 psi

Tensile Strength (Longitudinal): 2,870 psi



Brimar Stock Legends:

Sku#	Tape Copy
P3605	CAUTION CAUTION
P3617	CAUTION / CUIDADO (English/Spanish)
P3606	CAUTION OPEN TRENCH
P3607	CAUTION CONSTRUCTION AREA
P3608	CAUTION HARD HAT AREA
P3609	CAUTION NO SMOKING
P3610	CAUTION DO NOT ENTER
P3618	CAUTION DO NOT ENTER / CUIDADO NO ENTRE (English/Spanish)
P3611	CAUTION WET PAINT
P3612	CAUTION WET FLOOR
P3613	CAUTION MEN WORKING
P3615	CAUTION HIGH VOLTAGE
P3616	CAUTION NO PARKING

DATE: ___ / ___ / ___ **JOB:** _____

CONTRACTOR: _____