

## Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

# Barricade Tapes

*Increase Visibility Of Hazards And Prevent Accidents With Our Plastic Barricade Tapes*

### Tape Description:

- Our Barricade Tapes meet OSHA 1910.144 for marking physical hazards.
- Tape is a lightweight, economical, reusable polyethylene.
- Continuous repeat of warning message.
- Our barricade tapes can be tied, stapled or nailed in place.
- Tape consists of high visibility safety yellow polyethylene (plastic) with bold black letters.
- Indoor and Outdoor use.

**Tape Size:** 3in. x 1000 ft.

**Standard letter height:** 2 in.

**Material Thickness:** 4 Mil Polyethylene

**Tape Weight:** 4.5 lbs.

**Test Procedure:** ASTM-D-882, Method A

**Specimen Conditions:** 73°F / 50% R.H.

**Test Temperature:** 73°F

**Elongation:** 552%

**Tensile Strength (Transverse):** 2,100 psi

**Tensile Strength (Longitudinal):** 2,870 psi



### Brimar Stock Legends:

<b>Sku#</b>	<b>Tape Copy</b>
P3605	CAUTION CAUTION
P3617	CAUTION / CUIDADO (English/Spanish)
P3606	CAUTION OPEN TRENCH
P3607	CAUTION CONSTRUCTION AREA
P3608	CAUTION HARD HAT AREA
P3609	CAUTION NO SMOKING
P3610	CAUTION DO NOT ENTER
P3618	CAUTION DO NOT ENTER / CUIDADO NO ENTRE (English/Spanish)
P3611	CAUTION WET PAINT
P3612	CAUTION WET FLOOR
P3613	CAUTION MEN WORKING
P3615	CAUTION HIGH VOLTAGE
P3616	CAUTION NO PARKING

**DATE:** \_\_\_ / \_\_\_ / \_\_\_

**JOB:** \_\_\_\_\_

**CONTRACTOR:** \_\_\_\_\_