

## Product Information Bulletin

P.O. Box 467 | 64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

# PROMARK™ NAMEPLATES



## Reinforced Lexan & Polycarbonate Nameplate

**Material:**

Vinyl film sealed between 2 layers of polycarbonate

**Thickness:**

Combined thickness of .125"

**Use:**

Plates are used for the identification of piping & valve tags under harsh chemical and environmental conditions.

**Printed Image:**

Printed image is sealed between 2 layers of polycarbonate.

Legends can be configured to almost any size type and font on multiple lines if necessary.

**Mounting Method:**

Options of (4) Four 3/8", 1/4" or 3/16" Grommetted Holes or Pressure Sensitive Adhesive, or Foam Tape

**Durability:**

Indoor - Indefinite

Outdoor 5-8 years mid-continental United States

(Luminescent plates are not recommended for outdoor use)

**Chemical Resistance:**

Good for most chemicals

**Service Temperature:**

-40°F to 200°F.

**Dimensional Information:**

Plates are available in (5) five different sizes:

1 x 3", 2 x 3", 2 x 4", 3 x 6", & 4x 8". (Custom sizes available)

**COLORS AVAILABLE**

Background	Lettering
White	Black
Red	White
Yellow	Black
Blue	White
Green	White

**Letter Sizes:**

Letter sizes are determined by size of plate, number of lines, and number of characters per line. Can be sized to fit required character heights.

DATE: \_\_\_\_ / \_\_\_\_ / \_\_\_\_

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_